



For illustration purpose only



OIL COUNTRY LATHES

STANDART MACHINE SPECIFICATION

		Unit	C10T.14
CAPACITY	Height of centers	mm	510
	Swing over bed	mm	1020
	Swing over cross slide	mm	780
	Swing in gap	mm	1210
	Width of bed	mm	560
	Distance between centers	mm	1500;2000;3000;4000;5000;6000
SPINDLE	Spindle nose DIN 55026	No	A2.20
	Spindle bore	mm	358
HEAD STOCK	Number of spindle speeds		12
	Spindle variable speed sub-ranges	rpm	6,3 – 315
	Main motor power	kw	18,5
FEEDS	Number of feeds		152
	Longitudinal feed range	mm/rev	0,039 – 15
	Cross feed range	mm/rev	0,02 – 7,5
THREADS	Number of threads		4x64
	Metric thread range	mm	0,5 – 150
	Inch thread range	Tpi	60 – 1/5
	Module thread range	Module	0,125 – 37,5
	DP thread range	DP	240 – 4/5
CARRIAGE	Cross slide travel	mm	510
	Top slide travel	mm	280
TAIL STOCK	Quill diameter	mm	105
	Quill taper	Morse	No.6
	Quill travel	mm	225
WEIGHT	For DBC 2000 mm	kg	7100